

# SAFETY DATA SHEET.



Issuing date 03-Apr-2015

Revision Date 03-Apr-2015

Version 1

## 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

### Product identifier

**Product name** Vinyl, Plastic, & Carpet Dye –FLAGSTONE

### Recommended use of the chemical and restrictions on use

**Product code** HT 455

**Product Type** Extremely flammable aerosol  
**Synonyms** None

### Supplier's details

**Recommended Use** Dye.  
**Uses advised against** No information available

**Manufactured For:**  
Hi-Tech Industries  
33106 W. 8 Mile  
Farmington, MI 48336  
Company Telephone: 248-358-2626

**Chemical Emergency Phone Number** INFOTRAC 1-352-323-3500 (International)  
1-800-535-5053 (North America)





|                   |   |
|-------------------|---|
| <b>Inhalation</b> | Move to fresh air. If breathing is difficult, give oxygen. Artificial respiration and/or oxygen may be necessary. If breathing has stopped, contact emergency medical services immediately. |
| <b>Ingestion</b>  | Rinse mouth. Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Call a physician or Poison Control Center immediately.  |

**Most important symptoms/effects, acute and delayed**

|                      |   |
|----------------------|---|
| <b>Main Symptoms</b> | Causes skin and eye irritation. Irritating to respiratory system. May cause drowsiness or dizziness. May damage to fertility or the unborn child. May cause cancer. Harmful or fatal if swallowed and enters airways. Causes damage to organs through prolonged or repeated exposure. |
|----------------------|---|

**Indication of immediate medical attention and special treatment needed, if necessary**

|                           |                        |
|---------------------------|------------------------|
| <b>Notes to physician</b> | Treat symptomatically. |
|---------------------------|------------------------|

**5. FIRE-FIGHTING MEASURES****Suitable Extinguishing Media**

Foam, dry chemical, carbon dioxide, or fine water spray. Water fog. Dry chemical. Carbon dioxide (CO<sub>2</sub>). Cool containers/tanks with water spray.

**Unsuitable Extinguishing Media** Keep away from sources of ignition - No smoking. Cool containers / tanks with water spray.

**Specific hazards arising from the chemical**

In the event of fire and/or explosion do not breathe fumes. Extremely flammable. Keep product and empty container away from heat and sources of ignition.

**Explosion Data**

**Sensitivity to Mechanical Impact** none.

**Sensitivity to Static Discharge** Yes.

**Protective Equipment and Precautions for Firefighters**

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

**6. ACCIDENTAL RELEASE MEASURES****Personal precautions, protective equipment and emergency procedures**

|                             |   |
|-----------------------------|---|
| <b>Personal precautions</b> | Avoid contact with eyes. Avoid breathing vapors or mists. Contents under pressure. Do not puncture or incinerate cans. Do not stick pin or any other sharp object into opening on top of can. Avoid skin contact. Use with adequate ventilation. Keep container away from heat, flames, and all other sources of ignition. Keep can away from all sources of electricity such as electric motors and batteries. Do not spray on hot surfaces. |
|-----------------------------|---|

**Environmental precautions**

|                                  |   |
|----------------------------------|---|
| <b>Environmental precautions</b> | Beware of vapors accumulating to form explosive concentrations. Vapors can accumulate in low areas. Prevent further leakage or spillage if safe to do so. Do not allow material to contaminate ground water system. Prevent product from entering drains. Local authorities should be advised if significant spillages cannot be contained. |
|----------------------------------|---|

**Methods and materials for containment and cleaning up**

|                                |  |
|--------------------------------|--|
| <b>Methods for Containment</b> | Prevent further leakage or spillage if safe to do so. Absorb spill with inert material (e.g. dry sand or earth), then place in a chemical waste container. |
|--------------------------------|--|

**Methods for cleaning up** Pick up and transfer to properly labeled containers. Soak up with inert absorbent material. Clean contaminated surface thoroughly. After cleaning, flush away traces with water. Take precautionary measures against static discharges.

## 7. HANDLING AND STORAGE

### Precautions for safe handling

**Advice on safe handling** Avoid contact with eyes. Avoid breathing vapors or mists. Contents under pressure. Do not puncture or incinerate cans. Do not stick pin or any other sharp object into opening on top of can.

### Conditions for safe storage, including any incompatibilities

**Technical measures/Storage conditions** Keep container tightly closed in a dry and well-ventilated place. Keep away from open flames, hot surfaces and sources of ignition. Keep in properly labeled containers. Keep out of the reach of children. Store locked up.

**Incompatible products** Strong acids, alkalis, or oxidizing agents.

**Aerosol Level** 3

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Control parameters

#### Exposure Guidelines

| Chemical Name                            | ACGIH TLV   | OSHA PEL  | NIOSH IDLH   |
|--|---|---|--|
| ACETONE<br>67-64-1                       | STEL: 750 ppm<br>TWA: 500 ppm   | TWA: 1000 ppm<br>TWA: 2400 mg/m <sup>3</sup><br>(vacated) TWA: 750 ppm<br>(vacated) TWA: 1800 mg/m <sup>3</sup><br>(vacated) STEL: 2400 mg/m <sup>3</sup><br>The acetone STEL does not apply to the cellulose acetate fiber industry. It is in effect for all other sectors<br>(vacated) STEL: 1000 ppm | IDLH: 2500 ppm<br>TWA: 250 ppm<br>TWA: 590 mg/m <sup>3</sup>   |
| PROPANE/ISOBUTANE/N-BUTANE<br>68476-86-8 | 74-98-6: TWA: 1000 ppm<br>106-97-8: STEL: 1000 ppm<br>75-28-5: STEL: 1000 ppm | 74-98-6: TWA: 1000 ppm<br>TWA: 1800 mg/m <sup>3</sup><br>(vacated) TWA: 1000 ppm<br>(vacated) TWA: 1800 mg/m <sup>3</sup><br>106-97-8: (vacated) TWA: 800 ppm<br>(vacated) TWA: 1900 mg/m <sup>3</sup>  | 74-98-6: IDLH: 2100 ppm<br>TWA: 1000 ppm<br>TWA: 1800 mg/m <sup>3</sup><br>106-97-8: TWA: 800 ppm<br>TWA: 1900 mg/m <sup>3</sup><br>75-28-5: TWA: 800 ppm<br>TWA: 1900 mg/m <sup>3</sup> |
| TOLUENE<br>108-88-3                      | TWA: 20 ppm   | TWA: 200 ppm<br>(vacated) TWA: 100 ppm<br>(vacated) TWA: 375 mg/m <sup>3</sup><br>(vacated) STEL: 150 ppm<br>(vacated) STEL: 560 mg/m <sup>3</sup><br>Ceiling: 300 ppm  | IDLH: 500 ppm<br>TWA: 100 ppm<br>TWA: 375 mg/m <sup>3</sup><br>STEL: 150 ppm<br>STEL: 560 mg/m <sup>3</sup>  |
| N-BUTYL ALCOHOL<br>71-36-3               | TWA: 20 ppm   | TWA: 100 ppm<br>TWA: 300 mg/m <sup>3</sup><br>(vacated) S*<br>(vacated) Ceiling: 50 ppm<br>(vacated) Ceiling: 150 mg/m <sup>3</sup>   | IDLH: 1400 ppm<br>Ceiling: 50 ppm<br>Ceiling: 150 mg/m <sup>3</sup>  |
| 2-BUTANONE<br>78-93-3                    | STEL: 300 ppm<br>TWA: 200 ppm   | TWA: 200 ppm<br>TWA: 590 mg/m <sup>3</sup><br>(vacated) TWA: 200 ppm<br>(vacated) TWA: 590 mg/m <sup>3</sup><br>(vacated) STEL: 300 ppm<br>(vacated) STEL: 885 mg/m <sup>3</sup>  | IDLH: 3000 ppm<br>TWA: 200 ppm<br>TWA: 590 mg/m <sup>3</sup><br>STEL: 300 ppm<br>STEL: 885 mg/m <sup>3</sup>   |

|                                    |  |  |   |
|------------------------------------|--|--|---|
| CALCIUM CARBONATE<br>1317-65-3     | -  | TWA: 15 mg/m <sup>3</sup> total dust<br>TWA: 5 mg/m <sup>3</sup> respirable fraction<br>(vacated) TWA: 15 mg/m <sup>3</sup> total dust<br>(vacated) TWA: 5 mg/m <sup>3</sup> respirable fraction | TWA: 10 mg/m <sup>3</sup> total dust<br>TWA: 5 mg/m <sup>3</sup> respirable dust  |
| TITANIUM DIOXIDE<br>13463-67-7     | TWA: 10 mg/m <sup>3</sup>  | TWA: 15 mg/m <sup>3</sup> total dust<br>(vacated) TWA: 10 mg/m <sup>3</sup> total dust   | IDLH: 5000 mg/m <sup>3</sup>  |
| MAGNESIUM SILICATE<br>14807-96-6   | TWA: 2 mg/m <sup>3</sup> particulate matter containing no asbestos and <1% crystalline silica, respirable fraction | (vacated) TWA: 2 mg/m <sup>3</sup> respirable dust <1% Crystalline silica, containing no Asbestos<br>TWA: 20 mppcf if 1% Quartz or more, use Quartz limit  | IDLH: 1000 mg/m <sup>3</sup><br>TWA: 2 mg/m <sup>3</sup> containing no Asbestos and <1% Quartz respirable dust  |
| ETHYL BENZENE<br>100-41-4          | TWA: 20 ppm  | TWA: 100 ppm<br>TWA: 435 mg/m <sup>3</sup><br>(vacated) TWA: 100 ppm<br>(vacated) TWA: 435 mg/m <sup>3</sup><br>(vacated) STEL: 125 ppm<br>(vacated) STEL: 545 mg/m <sup>3</sup>                 | IDLH: 800 ppm<br>TWA: 100 ppm<br>TWA: 435 mg/m <sup>3</sup><br>STEL: 125 ppm<br>STEL: 545 mg/m <sup>3</sup>   |
| METHYL ISOBUTYL KETONE<br>108-10-1 | STEL: 75 ppm<br>TWA: 20 ppm  | TWA: 100 ppm<br>TWA: 410 mg/m <sup>3</sup><br>(vacated) TWA: 50 ppm<br>(vacated) TWA: 205 mg/m <sup>3</sup><br>(vacated) STEL: 75 ppm<br>(vacated) STEL: 300 mg/m <sup>3</sup>                   | IDLH: 500 ppm<br>TWA: 50 ppm<br>TWA: 205 mg/m <sup>3</sup><br>STEL: 75 ppm<br>STEL: 300 mg/m <sup>3</sup>   |
| XYLENE<br>1330-20-7                | STEL: 150 ppm<br>TWA: 100 ppm  | TWA: 100 ppm<br>TWA: 435 mg/m <sup>3</sup><br>(vacated) TWA: 100 ppm<br>(vacated) TWA: 435 mg/m <sup>3</sup><br>(vacated) STEL: 150 ppm<br>(vacated) STEL: 655 mg/m <sup>3</sup>                 | -   |
| CARBON BLACK<br>1333-86-4          | TWA: 3 mg/m <sup>3</sup> inhalable fraction  | TWA: 3.5 mg/m <sup>3</sup><br>(vacated) TWA: 3.5 mg/m <sup>3</sup>   | IDLH: 1750 mg/m <sup>3</sup><br>TWA: 3.5 mg/m <sup>3</sup><br>TWA: 0.1 mg/m <sup>3</sup> Carbon black in presence of Polycyclic aromatic hydrocarbons PAH |

ACGIH: (American Conference of Governmental Industrial Hygienists)

OSHA: (Occupational Safety & Health Administration)

NIOSH IDLH: Immediately Dangerous to Life or Health

**Other Exposure Guidelines** Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992).

**Exposure controls**

**Engineering Measures** Showers  
Eyewash stations  
Ventilation systems.

**Individual protection measures, such as personal protective equipment**

- Eye/Face Protection** Safety glasses with side-shields.
- Skin and body protection** Chemical resistant apron. Protective gloves.
- Respiratory protection** If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.

**Hygiene measures** Handle in accordance with good industrial hygiene and safety practice.

**9. PHYSICAL AND CHEMICAL PROPERTIES**

**Physical and chemical properties**

|   |                          |                                 |                          |
|---|--------------------------|---------------------------------|--------------------------|
| <b>Physical state</b>                         | Aerosol                  | <b>Odor</b>                     | Solvent                  |
| <b>Appearance</b>                             | opaque                   | <b>Odor Threshold</b>           | No information available |
| <b>Color</b>                                  | flagstone                |                                 |                          |
| <b><u>Property</u></b>                        | <b><u>Values</u></b>     | <b><u>Remarks • Methods</u></b> |                          |
| <b>pH</b>                                     | No information available |                                 |                          |
| <b>Melting/freezing point</b>                 | No information available |                                 |                          |
| <b>Boiling point/boiling range</b>            | No information available |                                 |                          |
| <b>Flash Point</b>                            | -97 °C / -142 °F         | Based on propellant             |                          |
| <b>Evaporation rate</b>                       | No information available |                                 |                          |
| <b>Flammability (solid, gas)</b>              | No information available |                                 |                          |
| <b>Flammability Limits in Air</b>             |                          |                                 |                          |
| <b>upper flammability limit</b>               | No information available |                                 |                          |
| <b>lower flammability limit</b>               | No information available |                                 |                          |
| <b>Vapor pressure</b>                         | No information available |                                 |                          |
| <b>Vapor density</b>                          | No information available |                                 |                          |
| <b>Specific Gravity</b>                       | 0.823                    |                                 |                          |
| <b>Water solubility</b>                       | Practically insoluble    |                                 |                          |
| <b>Partition coefficient: n-octanol/water</b> | No information available |                                 |                          |
| <b>Autoignition temperature</b>               | No information available | Not applicable                  |                          |
| <b>Decomposition temperature</b>              | No information available |                                 |                          |
| <b>Viscosity</b>                              | No information available |                                 |                          |
| <b>Explosive properties</b>                   | No information available |                                 |                          |

**Other information**

VOC Content(%) 54.4

## 10. STABILITY AND REACTIVITY

**Reactivity**

No data available

**Chemical stability**

Stable under recommended storage conditions.

**Possibility of hazardous reactions**

None under normal processing.

**Conditions to Avoid**

Extremes of temperature and direct sunlight.

**Incompatible Materials**

Strong acids, alkalis, or oxidizing agents.

**Hazardous Decomposition Products**

None known based on information supplied.

## 11. TOXICOLOGICAL INFORMATION

**Information on likely routes of exposure****Product Information****Inhalation**

Vapors may irritate throat and respiratory system. May cause drowsiness and dizziness based on components. May cause irritation of respiratory tract. Avoid breathing vapors or mists.

|                     |  |
|---------------------|--|
| <b>Eye contact</b>  | Irritating to eyes. Avoid contact with eyes.   |
| <b>Skin contact</b> | Irritating to skin. Avoid contact with skin. Repeated exposure may cause skin dryness or cracking. Prolonged skin contact may defat the skin and produce dermatitis. |
| <b>Ingestion</b>    | May be harmful if swallowed. Aspiration into the lungs during swallowing may cause serious lung damage which may be fatal.   |

**Component Information**

| Chemical Name                      | LD50 Oral             | LD50 Dermal              | LC50 Inhalation                       |
|------------------------------------|-----------------------|--------------------------|---------------------------------------|
| ACETONE<br>67-64-1                 | = 5800 mg/kg          | 20,000 mg/kg (Rabbit)    | = 50100 mg/m <sup>3</sup> ( Rat ) 8 h |
| TOLUENE<br>108-88-3                | = 2600 mg/kg ( Rat )  | = 12000 mg/kg ( Rabbit ) | = 12.5 mg/L ( Rat ) 4 h               |
| N-BUTYL ALCOHOL<br>71-36-3         | = 700 mg/kg ( Rat )   | = 3402 mg/kg ( Rabbit )  | > 8000 ppm ( Rat ) 4 h                |
| 2-BUTANONE<br>78-93-3              | = 2483 mg/kg ( Rat )  | = 5000 mg/kg ( Rabbit )  | = 11700 ppm ( Rat ) 4 h               |
| TITANIUM DIOXIDE<br>13463-67-7     | > 10000 mg/kg ( Rat ) | -                        | -                                     |
| ETHYL BENZENE<br>100-41-4          | -                     | = 15400 mg/kg ( Rabbit ) | -                                     |
| METHYL ISOBUTYL KETONE<br>108-10-1 | = 2080 mg/kg ( Rat )  | = 3000 mg/kg ( Rabbit )  | = 8.2 mg/L ( Rat ) 4 h                |
| XYLENE<br>1330-20-7                | = 3500 mg/kg ( Rat )  | > 4350 mg/kg ( Rabbit )  | = 29.08 mg/L ( Rat ) 4 h              |

**Information on toxicological effects**

|                 |  |
|-----------------|--|
| <b>Symptoms</b> | Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting. Irritating to respiratory system. Causes serious eye irritation. Irritating to skin. May be harmful or fatal if ingested. |
|-----------------|--|

**Delayed and immediate effects as well as chronic effects from short and long-term exposure**

|                                  |  |
|----------------------------------|--|
| <b>Skin corrosion/irritation</b> | Irritating to skin.  |
| <b>Eye damage/irritation</b>     | Irritating to eyes.  |
| <b>Irritation</b>                | Irritating to eyes, respiratory system and skin.   |
| <b>Sensitization</b>             | None known.  |
| <b>Germ Cell Mutagenicity</b>    | None known.  |
| <b>Carcinogenicity</b>           | The table below indicates whether each agency has evaluated a listed ingredient as a carcinogen. |

| Chemical Name                         | ACGIH | IARC     | NTP | OSHA |
|---------------------------------------|-------|----------|-----|------|
| TOLUENE<br>108-88-3                   | -     | Group 3  | -   | -    |
| TITANIUM DIOXIDE<br>13463-67-7        | -     | 2B       | -   | -    |
| MAGNESIUM SILICATE<br>14807-96-6      | -     | Group 3  | -   | -    |
| ETHYL BENZENE<br>100-41-4             | A3    | Group 2B | -   | -    |
| METHYL ISOBUTYL<br>KETONE<br>108-10-1 | A3    | Group 2B | -   | -    |
| XYLENE<br>1330-20-7                   | -     | Group 3  | -   | -    |
| CARBON BLACK<br>1333-86-4             | A3    | Group 2B | -   | -    |

**ACGIH:** (American Conference of Governmental Industrial Hygienists)

A3 - Animal Carcinogen

**IARC:** (International Agency for Research on Cancer)

Group 2B - Possibly Carcinogenic to Humans

Group 3 - Not Classifiable as to Carcinogenicity in Humans



**OSHA: (Occupational Safety & Health Administration)**

X - Present

|  |  |
|--|--|
| <b>Reproductive toxicity</b>                                       | Product is or contains a chemical which is a known or suspected reproductive hazard.                         |
| <b>Specific target organ systemic toxicity (single exposure)</b>   | May cause respiratory irritation. May cause drowsiness and dizziness.  |
| <b>Specific target organ systemic toxicity (repeated exposure)</b> | May cause damage to organs through prolonged or repeated exposure.   |
| <b>Chronic toxicity</b>  | May cause adverse liver effects.   |
| <b>Target Organ Effects</b>  | Central nervous system, Central Vascular System (CVS), Eyes, Kidney, Liver, Lungs, Respiratory system, Skin. |
| <b>Neurological effects</b>  | Intentional misuse by deliberately concentrating and inhaling contents may be harmful or fatal.              |
| <b>Aspiration hazard</b>   | May be fatal if swallowed and enters airways.  |

**Numerical measures of toxicity - Product Information**

**Unknown Acute Toxicity** 0% of the mixture consists of ingredient(s) of unknown toxicity

The following values are calculated based on chapter 3.1 of the GHS document .

|                                |             |
|--------------------------------|-------------|
| <b>ATEmix (oral)</b>           | 18100 mg/kg |
| <b>ATEmix (dermal)</b>         | 14699 mg/kg |
| <b>ATEmix (inhalation-gas)</b> | 646416 mg/l |

## 12. ECOLOGICAL INFORMATION

**Ecotoxicity**

| Chemical Name                            | Toxicity to algae   | Toxicity to fish   | Toxicity to microorganisms | Toxicity to daphnia and other aquatic invertebrates   |
|--|---|--|----------------------------|---|
| ACETONE<br>67-64-1                       | -   | 4.74 - 6.33 mL/L LC50<br>Oncorhynchus mykiss 96h<br>6210 - 8120 mg/L LC50<br>Pimephales promelas 96h<br>static 8300 mg/L LC50<br>Lepomis macrochirus 96h   | -                          | 10294 - 17704 mg/L EC50<br>Daphnia magna 48h Static<br>12600 - 12700 mg/L EC50<br>Daphnia magna 48h |
| PROPANE/ISOBUTANE/N-BUTANE<br>68476-86-8 | -   | -  | -                          | -   |
| TOLUENE<br>108-88-3                      | 433 mg/L EC50<br>Pseudokirchneriella<br>subcapitata 96h 12.5 mg/L<br>EC50 Pseudokirchneriella<br>subcapitata 72h static | 11.0 - 15.0 mg/L LC50<br>Lepomis macrochirus 96h<br>static 14.1 - 17.16 mg/L<br>LC50 Oncorhynchus mykiss<br>96h static 15.22 - 19.05 mg/L<br>LC50 Pimephales promelas<br>96h flow-through 5.89 - 7.81<br>mg/L LC50 Oncorhynchus<br>mykiss 96h flow-through<br>50.87 - 70.34 mg/L LC50<br>Poecilia reticulata 96h static<br>12.6 mg/L LC50 Pimephales<br>promelas 96h static 28.2<br>mg/L LC50 Poecilia<br>reticulata 96h semi-static 5.8<br>mg/L LC50 Oncorhynchus<br>mykiss 96h semi-static 54<br>mg/L LC50 Oryzias latipes<br>96h static | -                          | 5.46 - 9.83 mg/L EC50<br>Daphnia magna 48h Static<br>11.5 mg/L EC50 Daphnia<br>magna 48h            |
| N-BUTYL ALCOHOL<br>71-36-3               | 500 mg/L EC50<br>Desmodesmus subspicatus<br>96h 500 mg/L EC50<br>Desmodesmus subspicatus<br>72h                         | 100000 - 500000 µg/L LC50<br>Lepomis macrochirus 96h<br>static 1730 - 1910 mg/L<br>LC50 Pimephales promelas<br>96h static 1740 mg/L LC50<br>Pimephales promelas 96h<br>flow-through 1910000 µg/L<br>LC50 Pimephales promelas<br>96h static   | -                          | 1897 - 2072 mg/L EC50<br>Daphnia magna 48h Static<br>1983 mg/L EC50 Daphnia<br>magna 48h            |

|                                       |  |   |   |   |
|---------------------------------------|--|---|---|---|
| 2-BUTANONE<br>78-93-3                 | -  | 3130 - 3320 mg/L LC50<br>Pimephales promelas 96h<br>flow-through  | - | 4025 - 6440 mg/L EC50<br>Daphnia magna 48h Static<br>5091 mg/L EC50 Daphnia<br>magna 48h 520 mg/L EC50<br>Daphnia magna 48h |
| MAGNESIUM SILICATE<br>14807-96-6      | -  | 100 g/L LC50 Brachydanio<br>rerio 96h semi-static   | - | -   |
| ETHYL BENZENE<br>100-41-4             | 4.6 mg/L EC50<br>Pseudokirchneriella<br>subcapitata 72h 438 mg/L<br>EC50 Pseudokirchneriella<br>subcapitata 96h 2.6 - 11.3<br>mg/L EC50<br>Pseudokirchneriella<br>subcapitata 72h static 1.7 -<br>7.6 mg/L EC50<br>Pseudokirchneriella<br>subcapitata 96h static | 11.0 - 18.0 mg/L LC50<br>Oncorhynchus mykiss 96h<br>static 7.55 - 11 mg/L LC50<br>Pimephales promelas 96h<br>flow-through 9.1 - 15.6 mg/L<br>LC50 Pimephales promelas<br>96h static 32 mg/L LC50<br>Lepomis macrochirus 96h<br>static 4.2 mg/L LC50<br>Oncorhynchus mykiss 96h<br>semi-static 9.6 mg/L LC50<br>Poecilia reticulata 96h static   | - | 1.8 - 2.4 mg/L EC50 Daphnia<br>magna 48h  |
| METHYL ISOBUTYL<br>KETONE<br>108-10-1 | 400 mg/L EC50<br>Pseudokirchneriella<br>subcapitata 96h  | 496 - 514 mg/L LC50<br>Pimephales promelas 96h<br>flow-through  | - | 170 mg/L EC50 Daphnia<br>magna 48h  |
| XYLENE<br>1330-20-7                   | -  | 13.1 - 16.5 mg/L LC50<br>Lepomis macrochirus 96h<br>flow-through 13.5 - 17.3<br>mg/L LC50 Oncorhynchus<br>mykiss 96h 2.661 - 4.093<br>mg/L LC50 Oncorhynchus<br>mykiss 96h static 23.53 -<br>29.97 mg/L LC50<br>Pimephales promelas 96h<br>static 30.26 - 40.75 mg/L<br>LC50 Poecilia reticulata 96h<br>static 7.711 - 9.591 mg/L<br>LC50 Lepomis macrochirus<br>96h static 13.4 mg/L LC50<br>Pimephales promelas 96h<br>flow-through 19 mg/L LC50<br>Lepomis macrochirus 96h<br>780 mg/L LC50 Cyprinus<br>carpio 96h semi-static 780<br>mg/L LC50 Cyprinus carpio<br>96h | - | 0.6 mg/L LC50 Gammarus<br>lacustris 48h 3.82 mg/L<br>EC50 water flea 48h  |

**Persistence and degradability**

No information available.

**Bioaccumulation**

No information available.

| Chemical Name                            | log Pow |
|--|---------|
| ACETONE<br>67-64-1                       | -0.24   |
| PROPANE/ISOBUTANE/N-BUTANE<br>68476-86-8 | 2.8     |
| TOLUENE<br>108-88-3                      | 2.65    |
| N-BUTYL ALCOHOL<br>71-36-3               | 0.785   |
| 2-BUTANONE<br>78-93-3                    | 0.29    |
| ETHYL BENZENE<br>100-41-4                | 3.118   |
| METHYL ISOBUTYL KETONE<br>108-10-1       | 1.19    |
| XYLENE<br>1330-20-7                      | 3.15    |

Other adverse effects No information available

### 13. DISPOSAL CONSIDERATIONS

#### Waste treatment

**Waste Disposal Methods** This material, as supplied, is a hazardous waste according to federal regulations (40 CFR 261).

**Contaminated packaging** Do not re-use empty containers.

### 14. TRANSPORT INFORMATION

**DOT Ground** CONSUMER COMMODITY ORM-D  
or  
LIMITED QUANTITY

**IATA** UN1950, AEROSOLS, FLAMMABLE, 2.1, LTD. QTY.

**IMDG** UN1950, AEROSOLS, FLAMMABLE, 2.1, LTD. QTY.

### 15. REGULATORY INFORMATION

#### International Inventories

| Chemical Name                  | TSCA | DSL/NDL | EINECS/ELI<br>NCS | ENCS       | IECSC | KECL | PICCS | AICS |
|--------------------------------|------|---------|-------------------|------------|-------|------|-------|------|
| ACETONE                        | X    | X       | X                 | X          | X     | X    | X     | X    |
| PROPANE/ISOBUTAN<br>E/N-BUTANE | X    | X       | X                 | Not listed | X     | X    | X     | X    |
| TOLUENE                        | X    | X       | X                 | X          | X     | X    | X     | X    |
| N-BUTYL ALCOHOL                | X    | X       | X                 | X          | X     | X    | X     | X    |
| 2-BUTANONE                     | X    | X       | X                 | X          | X     | X    | X     | X    |
| CALCIUM<br>CARBONATE           | X    | X       | X                 | X          | X     | X    | X     | X    |
| TITANIUM DIOXIDE               | X    | X       | X                 | X          | X     | X    | X     | X    |
| MAGNESIUM<br>SILICATE          | X    | X       | X                 | X          | X     | X    | X     | X    |
| ETHYL BENZENE                  | X    | X       | X                 | X          | X     | X    | X     | X    |
| METHYL ISOBUTYL<br>KETONE      | X    | X       | X                 | X          | X     | X    | X     | X    |
| XYLENE                         | X    | X       | X                 | X          | X     | X    | X     | X    |
| CARBON BLACK                   | X    | X       | X                 | X          | X     | X    | X     | X    |

#### Legend:

**TSCA** - United States Toxic Substances Control Act Section 8(b) Inventory

**DSL/NDL** - Canadian Domestic Substances List/Non-Domestic Substances List

**EINECS/ELINCS** - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

**ENCS** - Japan Existing and New Chemical Substances

**CHINA** - China Inventory of Existing Chemical Substances

**KECL** - Korean Existing and Evaluated Chemical Substances

**PICCS** - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

**U.S. Federal Regulations****SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372:

| Chemical Name                     | CAS-No    | Weight %* | SARA 313 - Threshold Values % |
|-----------------------------------|-----------|-----------|-------------------------------|
| TOLUENE - 108-88-3                | 108-88-3  | 10-20     | 1.0                           |
| N-BUTYL ALCOHOL - 71-36-3         | 71-36-3   | 1-10      | 1.0                           |
| ETHYL BENZENE - 100-41-4          | 100-41-4  | 0.1-1     | 0.1                           |
| METHYL ISOBUTYL KETONE - 108-10-1 | 108-10-1  | 0.1-1     | 1.0                           |
| XYLENE - 1330-20-7                | 1330-20-7 | 0.1-1     | 1.0                           |

**SARA 311/312 Hazard Categories**

|                                   |     |
|-----------------------------------|-----|
| Acute Health Hazard               | Yes |
| Chronic Health Hazard             | Yes |
| Fire Hazard                       | Yes |
| Sudden Release of Pressure Hazard | Yes |
| Reactive Hazard                   | no  |

**Clean Water Act**

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42):

| Chemical Name             | CWA - Reportable Quantities | CWA - Toxic Pollutants | CWA - Priority Pollutants | CWA - Hazardous Substances |
|---------------------------|-----------------------------|------------------------|---------------------------|----------------------------|
| TOLUENE<br>108-88-3       | 1000 lb                     | X                      | X                         | X                          |
| ETHYL BENZENE<br>100-41-4 | 1000 lb                     | X                      | X                         | X                          |
| XYLENE<br>1330-20-7       | 100 lb                      |                        |                           | X                          |

**CERCLA**

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302):

| Chemical Name                      | Hazardous Substances RQs | Extremely Hazardous Substances RQs | RQ   |
|------------------------------------|--------------------------|------------------------------------|--|
| ACETONE<br>67-64-1                 | 5000 lb                  |                                    | RQ 5000 lb final RQ<br>RQ 2270 kg final RQ   |
| TOLUENE<br>108-88-3                | 1000 lb 1 lb             |                                    | RQ 1000 lb final RQ<br>RQ 454 kg final RQ RQ 1 lb final RQ<br>RQ 0.454 kg final RQ |
| N-BUTYL ALCOHOL<br>71-36-3         | 5000 lb                  |                                    | RQ 5000 lb final RQ<br>RQ 2270 kg final RQ   |
| 2-BUTANONE<br>78-93-3              | 5000 lb                  |                                    | RQ 5000 lb final RQ<br>RQ 2270 kg final RQ   |
| ETHYL BENZENE<br>100-41-4          | 1000 lb                  |                                    | RQ 1000 lb final RQ<br>RQ 454 kg final RQ  |
| METHYL ISOBUTYL KETONE<br>108-10-1 | 5000 lb                  |                                    | RQ 5000 lb final RQ<br>RQ 2270 kg final RQ   |
| XYLENE<br>1330-20-7                | 100 lb                   |                                    | RQ 100 lb final RQ<br>RQ 45.4 kg final RQ  |

**U.S. State Regulations****California Proposition 65**

This product contains the following Proposition 65 chemicals:

| Chemical Name | California Prop. 65 |
|---------------|---------------------|
|               |                     |

|                                   |                                      |
|-----------------------------------|--------------------------------------|
| TOLUENE - 108-88-3                | Developmental<br>Female Reproductive |
| TITANIUM DIOXIDE - 13463-67-7     | Carcinogen                           |
| ETHYL BENZENE - 100-41-4          | Carcinogen                           |
| METHYL ISOBUTYL KETONE - 108-10-1 | Carcinogen<br>Developmental          |
| CARBON BLACK - 1333-86-4          | Carcinogen                           |

**U.S. State Right-to-Know Regulations**

| Chemical Name                      | New Jersey | Massachusetts | Pennsylvania |
|------------------------------------|------------|---------------|--------------|
| ACETONE<br>67-64-1                 | X          | X             | X            |
| TOLUENE<br>108-88-3                | X          | X             | X            |
| N-BUTYL ALCOHOL<br>71-36-3         | X          | X             | X            |
| 2-BUTANONE<br>78-93-3              | X          | X             | X            |
| CALCIUM CARBONATE<br>1317-65-3     | X          | X             | X            |
| TITANIUM DIOXIDE<br>13463-67-7     | X          | X             | X            |
| MAGNESIUM SILICATE<br>14807-96-6   | X          | X             | X            |
| ETHYL BENZENE<br>100-41-4          | X          | X             | X            |
| METHYL ISOBUTYL KETONE<br>108-10-1 | X          | X             | X            |
| XYLENE<br>1330-20-7                | X          | X             | X            |
| CARBON BLACK<br>1333-86-4          | X          | X             | X            |

EPA Pesticide Registration Number Not applicable

**Canada**

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all the information required by the CPR.



**16. OTHER INFORMATION**

|                    |                 |                |                   |                                 |
|--------------------|-----------------|----------------|-------------------|---------------------------------|
| <b><u>NFPA</u></b> | Health Hazard 2 | Flammability 4 | Instability 0     | Physical and chemical hazards - |
| <b><u>HMIS</u></b> | Health Hazard 2 | Flammability 4 | Physical Hazard 1 | Personal protection B           |

Prepared By Regulatory Affairs  
 Issuing date 03-Apr-2015  
 Revision Date 03-Apr-2015  
 Revision Note  
 No information available

**Disclaimer**

The information provided on this SDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

**End of Safety Data Sheet**